



New Guard Coatings Group

□ A global reputation to protect.

The information herewith is given with the best of New Guard Coatings Group knowledge.

Rights are reserved to change and update the data without notice.

This information is not exhaustive and it is the user's responsibility to ensure that this data sheet is the most current by contacting their local New Guard Coatings Group branch prior to using the coating/product.

• USA •



www.newguardcoatings.com

 usasales@newguardcoatings.com

 +1 (302) 257 5760

Jotun Thinner No. 17

Product description

This is a paint thinner. Designed to improve the flow of a range of Jotun epoxy products. Can also be used as cleaner for pumps and tools before and after painting.

Typical use

Specially suitable as thinner for epoxies and similar type products except Tankguard series. Recommended usage as per technical datasheet or application guide for the specific product to be applied.

When thinners are used as a cleaning solvent, the use must be in accordance with prevailing local regulations.

Colors

clear

Product data

| Property | Test/Standard | Description |
|------------------|-------------------|---------------|
| Solids by volume | ISO 3233 | 0 % |
| Flash point | ISO 3679 Method 1 | 77 °F (25 °C) |
| Density | calculated | 0.9 kg/l |

| Region | Regulation | Test Standard | VOC Value |
|--------|----------------------------------|---------------|--------------|
| US | CARB(SCM)2020 / SCAQMD rule 1113 | Calculated | 7.23 lbs/gal |

The provided data is typical for factory produced products, subject to slight variation depending on color.

Packaging (typical)

| | Volume (liters) | Size of containers (liters) |
|----------------------|----------------------------|--|
| Jotun Thinner No. 17 | 5 / 20 | 5 / 20 |

The volume stated is for factory made colors. Note that local variants in pack size and filled volumes can vary due to local regulations.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, shaded, cool, well-ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 73°F (23 °C)

| | |
|----------------------|-------------|
| Jotun Thinner No. 17 | 48 month(s) |
|----------------------|-------------|

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Note

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Color variation

When applicable, products primarily meant for use as primers or antifoulings may have slight color variations from batch to batch. Such products and epoxy based products used as a finish coat may chalk when exposed to sunlight and weathering.

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., application quality and generic type of paint. Contact your local Jotun office for further information.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.
